

Data Sheet

GX-A

BIZERBA

The Smart Super Hybrid Sensor (Smart SHS) combines the advantages of EMFR load cells and strain gauge technology (DMS) with single-point load transmission. Your benefits with this ultimate technology: Very quick reaction with a stabilization time of only one to two seconds.



More information
High performance
with a wide range of
solutions and options.

Product description

Save time and money with the device-internal calibration with integrated calibration weight. Eliminate high costs, great time investment and demanding handling of external calibration weights.

Increase counting accuracy automatically: ACAI allows a more precise piece counting by permanently recalculating the average piece weight. This avoids system errors resulting from piece weight fluctuations.

The reaction time regulates itself automatically to FAST, MID, or SLOW depending on the environmental conditions.



GX-A

Highlights

- Backlit LCD display
- Automatic self-calibration: Automatic calibration in case of temperature changes
- Calibration at the touch of a button
- GLP/GMP/GCP/ISO compliant



GX-A

Options

- Analog output/current loop output
- Glass breeze break for models with weighing pans 128 x 128 mm and 165 x 165 mm
- Rechargeable battery pack
- Dust cover
- Density determination kit (GX-13)

My Bizerba

We offer you solutions from a single source which can be customized and allow you to respond to any change in a flexible manner. Benefit from costs which can be planned and efficient processes. We are happy to advise you.

Bizerba SE & Co. KG
Wilhelm-Kraut-Straße 65
72336 Balingen

T +49 7433 12-0
fax: +49 7433 12-2696
marketing@bizerba.com

www.bizerba.com