

Fact Sheet

GLM-levo 100V

BIZERBA

GLM-levo – the standard in the field of labeling. "The Big 3": Performance, Plug-I® label and Quality-Check-Inside – This is the outstanding benefit for your future requirements in price and product labeling.



More information
High performance
with a wide range of
solutions and options.

Specifications	Facts	Details
Weighing ranges	6 kg 15 kg 6/15 kg	Verification scale interval 2 g, min. FPV 500 g Verification scale interval 5 g, min. FPV 2,500 g Verification scale interval 2/5 g, min. prepack regulations (FPV) 500/2,500 g
Weighing belt dimensions	W 400 mm x L 500 mm	
Printing technology	Printing method Resolution Print width Print speed Label output	Thermal direct (optionally thermal transfer) 8 dot/mm (optional 12 dot/mm) 80 mm (optionally 104 mm, 168mm) max. 300 mm/s 120 mm
Labeler	Label size Label roll Thermal transfer ribbon	Min. W 30 mm x H 30 mm to W 120 mm x H 150 mm (depending on applicator type) Core diameter 76 mm (optionally 74 - 82 mm, 99 - 107 mm) Outer diameter 300 mm Core diameter 25.4 mm Outer diameter 81 mm
Labeling technology	Air-jet applicator Piston applicator Rotary applicator	Compressed air supply 6 bar, for top or bottom labeler Compressed air supply 2 bar, for top or bottom labeler
Labeler setting	Height adjustment Lateral adjustment	manual manual
Package size	min. W 40 mm x L 40 mm x H >1 mm Max. W 400 mm L x 500 mm H x 250 mm	
Labeling capacity	max. 100 ppm	Depending on device version, weight, package type and label size
Barcode versions	all common barcode versions	EAN/UPC 8, EAN/UPC 13, EAN/UPC 128, Code 2/5 int. Code 39, Code 128, GS1-128, PDF 417, PDF 417 with AI, GS1 DataBar Omni, GS1 DataBar, Data Matrix, QR code
Mains voltage	400 V/50 Hz 208 V/60 Hz	3*-phased
Operating temperature	0 °C to 40 °C	Stand-by up to -10 °C
Humidity	20 - 90%, non-condensing	
IP rating	IP20 IP54	Printers Scale, transport, control cabinet

Memory	500 MB	Compact Flash card
Operating unit	12" color touchscreen	optional industrial PC iS75 Operating concept with one or several displays possible

Options	Facts	Details
I/O 8 inputs		
I/O 8 outputs		
Tendency control		incl. license Tendency_Control, I/O card and 2 relays

Symbols



UNICODE WS Food Plug-in-label Industry 4.0

Dimensional drawings

Bizerba SE & Co. KG
 Wilhelm-Kraut-Straße 65
 72336 Balingen

T +49 7433 12-0
 fax: +49 7433 12-2696
 marketing@bizerba.com

www.bizerba.com